

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
10 January 2002 (10.01.2002)


PCT

(10) International Publication Number  
**WO 02/02991 A1**

- (51) International Patent Classification?: **F23D 14/06, F24C 3/08**
- (21) International Application Number: **PCT/IB01/01053**
- (22) International Filing Date: **15 June 2001 (15.06.2001)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
**MI2000A001523 6 July 2000 (06.07.2000) IT**
- (71) Applicant (for all designated States except US): **SABAF S.P.A. [IT/IT]; Via Rango, 23, I-25065 Lumezzane (IT).**
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **BETTINZOLI, Angelo [IT/IT]; Via Donizetti, 25, I-25062 Concesio (IT).**
- (74) Agent: **MARIETTI, Giuseppe; Marietti, Gislon e Trupiano S.r.l., Via Larga, 16, I-20122 Milan (IT).**
- (81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.**
- (84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).**

[Continued on next page]

(54) Title: **BURNER WITH INTERNAL SEPARATOR**



(57) Abstract: The invention relates to a burner (1) for cookers, suitable for burning gas, comprising at least two gas crowns, of which one central one and at least one circumferential one, a mixing chamber (13) with Venturi effect, ducts for entry of the primary air and radial ducts (9) for feeding the gas/primary air mixture to the said at least one circumferential crown, comprising a body (3), a head (2) and a separation element (4) that breaks up the internal space into ducts for entry of the primary air and ducts for distribution of the gas/primary air mixture.

WO 02/02991 A1

Best Available Copy

WO 02/02991 A1



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**"Burner with internal separator"****Technical Field**

The present invention relates to a burner for cookers equipped with two or more gas crowns, more in particular a burner suitable for use in built-in cooking surfaces.

**Background Art**

There are known burners for cookers provided with two or three gas crowns, in particular burners with three crowns, a central one and two outer ones, one facing the inside and one facing the outside of the burner.

This type of burner enables uniform heating of the pans that are set on them irrespective of the shape and size of the pans.

In the European patent application EP 0 797 048 in the name of the present applicant, a burner with three gas crowns is described which is provided with a horizontal Venturi made in a chamber formed between a base of the burner and an upper portion comprising the central gas crown. The chamber of the Venturi communicates with an upper chamber defined by the bottom of the area of central crown and by the central burner cap. This burner is substantially formed by three die-cast pieces which are then assembled together.

In the European patent application 0 903 538 in the name of the present applicant, an improved burner is described, which likewise has the characteristic of comprising three concentric gas crowns and means for feeding the gas/primary air mixture to said crowns. The said burner is made up of just two die-cast pieces, and the chamber with Venturi effect, which is substantially horizontal, is defined by the surfaces set facing one another, one of which corresponding to the body of the burner and the other to the cap of the central gas crown. Notwithstanding the advantage of being made up of just two die-cast

pieces, this burner presents, however, certain drawbacks; in particular, using just two die-cast pieces it is not possible to make, inside the burner, all the ducts necessary for the passage of the primary air and of the gas/primary air mixture. In fact, in this burner, the ducts that  
5 carry the gas/primary air mixture from the mixing chamber to the circumferential crowns are not altogether made in the body of the burner, but are defined by ducts delimited at the top only by planar appendages that join the central cap to the annular burner cap, a solution which is not ideal given the consequent inevitable leakages of  
10 mixture and the possibility of undesired displacements of said burner caps.

#### **Disclosure of Invention**

The purpose of the present invention is to overcome the drawbacks presented by the burners described above by providing a burner  
15 made up of just two die-cast pieces and equipped with the ducts for distributing the gas/primary air mixture from the mixing chamber to the circumferential crowns made inside the burner itself.

According to one aspect, the invention relates to a burner for built-in cookers, suitable for burning gas, comprising two or more gas crowns,  
20 of which one central one and at least one circumferential one, comprising a body and a head separated by a substantially flat element which breaks up the internal space into ducts for entry of the primary air and into ducts for the distribution of the gas/primary air mixture.

25 According to a main aspect, the invention thus relates to a burner as described in Claim 1.

In particular, the invention relates to a burner for cookers, suitable for burning gas, comprising at least two gas crowns, of which a central one and at least one circumferential one, a central mixing chamber

with Venturi effect, ducts for entry of the primary air, and radial ducts for feeding the gas/primary air mixture to the said at least one circumferential crown, characterized in that it comprises a body, a head, and a substantially flat internal element of separation designed to define the upper surfaces of said ducts for entry of the primary air and the lower surfaces of said radial ducts.

Preferred features of the burner of the invention are described in the dependent claims.

The invention will now be described in greater detail with particular reference to the attached figures exclusively by way of illustrative example.

#### **Brief Description of Drawings**

Figure 1 is an exploded view of a burner according to the invention.

Figure 2 is a view of the burner from above.

Figure 3 is a view of the burner from below.

Figure 4 is the section A-A of Figure 2.

Figure 4a is a schematic view of one half of the burner illustrated in Figure 4.

Figure 5 is a detail of the section C-C of Figure 4a.

Figure 6 is the section B-B of Figure 2; and

Figure 7 is a sectional view of a burner according to another embodiment of the present invention.

#### **Best mode for carrying out the invention**

With reference to Figure 1, a burner 1 according to the invention is shown which comprises a body 2, a head 3 and an interposed flat element 4; in the specific embodiment the interposed flat element 4 is shaped like a Celtic cross. Visible in the top portion of the head 3 are the central chamber 5 and the annular chamber 6 with the respective (central and circumferential) gas crowns which are covered with

respective caps 7 and 8. The central chamber is connected to the annular chamber 6 by means of the radial ducts 9, the top and side walls of which are defined in the head 2, and the bottom walls of which are defined by the upper surface of the flat element 4, which is  
5 joined to the head 2 by means of screws or studs deformed by upsetting (studs being preferred). A possible skirt 12 protects the slits designed for the entry of primary air; in some embodiments this skirt may not be present, or alternatively it may be joined to the flat element 4. A seal element 10 may be present for recessing of the  
10 burner into pyroceram hobs. Recessing of the burner in the surface 11 is obtained by using conventional means, and appropriate optional elements may be used for recessing.

With reference to Figure 2, the arrangement of the concentric gas crowns with the respective caps 7 and 8 is shown.

15 Figure 3 shows a view from below of the burner and illustrates the feed of the gas by means of the duct 15.

Figure 4 shows the internal conformation of the body and of the head of the burner, in particular the feed duct 15, the nozzle 16 in the body 2, and the structure of the Venturi channel 13, 13a, of the possible skirt  
20 12 and of blocking elements 17 for blocking the caps on the head 3.

Figure 4a shows schematically, and for just one half, the diametral section of the burner of Figure 2. In particular it may be noted that, in the body 2, there are ribs 18 which engage with complementary ribs 19 located on the head 3. The ribs 18 and 19, which are joined  
25 together when the burner is assembled, define channels communicating with the outside. The flat element 4 divides in the horizontal direction said channels into two, so breaking up the internal space and giving rise, at the bottom, to the ducts for entry of the primary air and, at the top, to the radial ducts 9 for distribution of the

gas/primary air mixture to the annular chamber 14. The arrows indicate the path of the air at entry and after mixing with the gas that comes from the nozzle 16.

With reference to Figure 5, it may be noted how the element 4 acts as  
5 internal separator defining two cavities, one for entry of the primary air indicated by the reference I and the other for the exit of the gas/primary air mixture in the annular chamber indicated by the reference M; also clearly visible in Figure 5 are the ribs 18 and 19 and the ducts that they define.

10 With reference to Figure 6, the parts making up the inside of the burner shown according to a different section are visible.

For operation of the burner, and again with reference to the specific technical solution illustrated in the figures, the primary air that penetrates through the slits made under the possible skirt 12 as  
15 indicated by the arrows is sucked into the Venturi channel 13, 13a, where it is mixed with the gas coming from the duct 5 and introduced by means of the nozzle 16. The gas/primary air mixture then ascends along the vertical and horizontal Venturi channel to reach the central crown underneath the central cap 7; from here, traversing the radial  
20 channels, as indicated by the arrows in Figure 4a, it reaches the annular chamber 14 and the overlying crowns.

As has been said, the body and the head are preferably die-cast as in conventional burners.

The internal element 4 is preferably made of a piece of steel sheet  
25 and may assume different shapes, according to the conformation of the body and head of the burner. According to an advantageous feature, the element 4 is shaped like a Celtic cross to define four internal ducts and a circular area of separation of the internal space adjacent to the Venturi channel.

As has been seen previously, the element 4 may alternatively be made of a single piece with the skirt.

According to a preferred aspect, the central chamber, which prevalently has a horizontal Venturi effect, is defined by the surfaces set facing one another, one of which corresponds to the body of the burner and the other to the cap of the central gas crown.

The gas crowns of the burner may assume different conformations; according to a preferred embodiment, however, the gas crown is obtained by means of holes positioned on the upper edge of the external walls of the central chamber.

As clearly described later with reference to figure 7, the flame holes 201 of the central flame crown are tilted with respect to the vertical axis Y of the burner at an angle  $\beta$  of between 40 and 70 degrees. The tilt of the flame holes 201 was found to be particular efficient in order to obtain stable flames and uniform distribution of the heat over the burner.

Advantageously, the circumferential gas crowns are two in number and have notches on the internal and external edges of the annular chamber as described, for example, in the European patent application 0 903 538 in the name of the present applicant.

The caps 7 and 8 and/or the skirt 12, which is possibly present, may be made of different materials, for example steel or brass, and may, moreover, be enamelled in various chromatic shades according to the different ornamental requirements.

Thanks to the specific internal conformation, and in particular to the separation element 4 set between the two die-cast pieces 2 and 3, the burner of the invention represents a clear improvement with respect to known burners, overcoming the problems that these present and enabling production at contained costs.



## EXAMPLE


With reference now to figure 7, showing an example of embodiment of the present invention, the burner body 102 and the burner head 103 are made in aluminium alloy (Al-Si and/or Al-Ni) or brass by die-casting and the flat internal element 109 is obtained by drawing a steel, stainless steel, or brass sheet.

Furthermore, the holes 201 of the central flame crown are realized on the peripheral wall of the central chamber 105 and they are tilted with respect to the vertical axis Y of the burner at an angle  $\beta$  of between 40 and 70 degrees.

## CLAIMS

1. A burner for cookers, suitable for burning gas, comprising at least two gas crowns, of which one central crown and at least one circumferential crown, a mixing chamber with Venturi effect, ducts for  
5 entry of the primary air, and radial ducts for feeding the gas/primary air mixture to the said at least one circumferential crown, characterized in that it comprises a body (2), a head (3) and a separation element (4) which breaks up the internal space into ducts (I) for entry of the primary air and ducts (9, M) for distribution of the  
10 gas/primary air mixture.
2. The burner according to Claim 1, in which said separation element is made of steel sheet.
3. The burner according to Claim 1 or Claim 2, in which the top and side walls of said radial ducts (9) are defined in the head (3), and  
15 the bottom walls are defined by the upper surface of the separation element (4).
4. The burner according to the any of the preceding claims, in which the body (2) is equipped with ribs (18) that engage with ribs (19) which branch off from the head (3), defining channels  
20 communicating with the outside.
5. The burner according to the previous claim, in which the flat element (4) divides into two, in the horizontal direction, said channels communicating with the outside, so breaking up the internal space and defining, at the bottom, said ducts for entry of the primary air (I) and, at the top, said radial ducts (9, M).  
25
6. The burner according to any of the preceding claims, in which said ducts for entry of the primary air and said ducts for the distribution of the gas/primary air mixture are four in number, arranged in the form of a cross.

7. The burner according to any of the preceding claims, in which said separation element is shaped like a Celtic cross.
8. The burner according to any of the preceding claims, in which said separation element is joined to the skirt (12).
- 5 9. The burner according to Claim 1 or Claim 2, in which the caps (7) and (8) and the possible skirt (12) are made of steel or brass and are possibly enamelled in different chromatic shades.
- 10 10. The burner according to any of the preceding Claims, characterised in that flame holes (201) of the central flame crown are tilted with respect to the vertical axis (Y) of the burner at an angle in the range of 40 to 70 degrees.



**Fig. 1**

Fig. 2




Fig. 3





Fig. 4








Fig. 5





Fig. 6






Fig. 7

## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/IB 01/01053

A. CLASSIFICATION OF SUBJECT MATTER  
 IPC 7 F23D14/06 F24C3/08

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F23D F24C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages  | Relevant to claim No. |
|------------|---|-----------------------|
| X          | EP 0 797 048 A (SABAF SPA)<br>24 September 1997 (1997-09-24)<br>cited in the application<br>figures 4,5<br>column 3, line 3 - line 34 | 1,3,5-7               |
| Y          |   | 8-10                  |
| A          |   | 4                     |
| Y          | EP 0.908 682 A (SABAF SPA)<br>14 April 1999 (1999-04-14)<br>figure 1<br>column 2, line 57 -column 3, line 22<br>-/--                  | 8,9                   |

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- \*G\* document member of the same patent family

Date of the actual completion of the international search

21 September 2001

Date of mailing of the international search report

27/09/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
 NL - 2280 HV Rijswijk  
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
 Fax: (+31-70) 340-3016

Authorized officer

Mougey, M

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/IB 01/01053

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages  | Relevant to claim No. |
|------------|---|-----------------------|
| Y          | PATENT ABSTRACTS OF JAPAN<br>vol. 1999, no. 10,<br>31 August 1999 (1999-08-31)<br>& JP 11 125405 A (OSAKA GAS CO LTD),<br>11 May 1999 (1999-05-11)<br>abstract<br>----                | 10                    |
| A          | WO 99 11975 A (ESKILDSSEN CHRISTIAN<br>;ARMANNI PIERO (IT); ELECTROLUX AB (SE))<br>11 March 1999 (1999-03-11)<br>page 2, line 12 - line 32<br>page 4, line 16 -page 5, line 3<br>---- | 1,2                   |
| A          | EP 0 634 608 A (DEFENDI OFF MEC SRL)<br>18 January 1995 (1995-01-18)<br>column 2, line 16 -column 3, line 17<br>figures 1,4<br>----   | 1,6,7                 |
| A          | EP 0 903 538 A (SABAF SPA)<br>24 March 1999 (1999-03-24)<br>cited in the application<br>the whole document<br>----  | 1,6,7                 |
| A          | EP 0 945 679 A (GAZ DE FRANCE)<br>29 September 1999 (1999-09-29)<br>page 1, line 30 - line 31<br>-----  | 9                     |

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No  
PCT/IB 01/01053

| Patent document<br>cited in search report |   | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|---|---|---------------------|----------------------------|---------------------|
| EP 0797048                                | A | 24-09-1997          | EP 0797048 A1              | 24-09-1997          |
|   |   |                     | PL 319027 A1               | 29-09-1997          |
|   |   |                     | SI 797048 T1               | 31-12-1999          |
|   |   |                     | TR 9700179 A1              | 21-10-1997          |
|   |   |                     | AT 184384 T                | 15-09-1999          |
|   |   |                     | DE 69604153 D1             | 14-10-1999          |
|   |   |                     | DE 69604153 T2             | 25-05-2000          |
|   |   |                     | DE 797048 T1               | 12-03-1998          |
|   |   |                     | ES 2107401 T1              | 01-12-1997          |
| EP 0908682                                | A | 14-04-1999          | EP 0908682 A1              | 14-04-1999          |
|   |   |                     | AU 8709498 A               | 29-04-1999          |
|   |   |                     | BR 9804172 A               | 22-05-2001          |
|   |   |                     | CA 2247713 A1              | 08-04-1999          |
|   |   |                     | PL 329091 A1               | 12-04-1999          |
|   |   |                     | TR 9802012 A2              | 21-04-1999          |
|   |   |                     | US 6030207 A               | 29-02-2000          |
| JP 11125405                               | A | 11-05-1999          | NONE                       |                     |
| WO 9911975                                | A | 11-03-1999          | WO 9911975 A1              | 11-03-1999          |
|   |   |                     | AU 3939497 A               | 22-03-1999          |
|   |   |                     | EP 1025392 A1              | 09-08-2000          |
| EP 0634608                                | A | 18-01-1995          | IT VE930018 A1             | 16-01-1995          |
|   |   |                     | EP 0634608 A2              | 18-01-1995          |
| EP 0903538                                | A | 24-03-1999          | EP 0903538 A1              | 24-03-1999          |
|   |   |                     | CA 2245513 A1              | 23-03-1999          |
|   |   |                     | CN 1212348 A               | 31-03-1999          |
|   |   |                     | PL 328145 A1               | 29-03-1999          |
|   |   |                     | TR 9801888 A2              | 21-04-1999          |
|   |   |                     | US 6035846 A               | 14-03-2000          |
| EP 0945679                                | A | 29-09-1999          | FR 2776753 A1              | 01-10-1999          |
|   |   |                     | EP 0945679 A1              | 29-09-1999          |
|   |   |                     | NO 991453 A                | 27-09-1999          |
|   |   |                     | TR 9900646 A2              | 21-10-1999          |
|   |   |                     | US 6082994 A               | 04-07-2000          |

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☒ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☒ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☒ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**